

M-6028

FEATURES

- Factory tested
- Available in Left & Right Models
- Black/ tempered glass walls
- Phone
- FM Radio
- Steam Aromatherapy Cup
- Body Massage Jets
- Rainfall Shower
- Hand-held Shower w/ Height-Adjustable Bracket
- Bench
- Pressure Balance Valve (On Request)
- Thermostatic Valve
- Adjustable Time Settings
- Control Panel with Remote
- Hinged Door
- Circulation Fan
- Chromo-therapy lighting
- Self-Cleaning Steam Generator
- Stone composite base
- Assembly from inside the unit
- Caulk free



TECHNICAL INFORMATION

- **Materials:** Tempered Glass
- **Power Supply:** 220V, 3KW
- **Steam Ready:** 2-5 MIN
- **Dimensions:** 59 x 40 x 86 IN

ELECTRICAL REQUIREMENTS

- Steam box- 3 KW
- 1 dedicated 12-2 line for steam (line 1, line 2, and ground)
- 220 volt, 20 amp GFCI breaker
- There is a length of wire from the steam box supplied to connect to power source.

PLUMBING REQUIREMENTS

- The unit is equipped with hot and cold, metal braided ½ inch water supply hose with ½ national pipe thread.
- Need to install hot and cold shutoffs with ½ -male national pipe thread (not included).
- Supply hoses are to connect from the faucet manifold on the unit to the shutoff valves.
- All water jet features are pre plumbed with reinforced braided flexible supply hose
- All fixtures and fittings should be checked for tightness as they may have been loosened during transport. It is advised to have base onsite before preparing drain location.

GENERAL INFORMATION

- Units come broken down in panels and are assembled with screws, nuts and bolts on site.
- This unit assembles from the -inside for convenience.
- **Note:** All shower bases are a man made stone composite and may need to be set in mortar for leveling purposes.
- It is advised to have base onsite before preparing drain location.