

MK-547

FEATURES



- Factory tested
- Corner Unit
- Available in Bone or White
- Polished Finish
- FM Radio
- Steam Aromatherapy Cup
- Accessory Rack
- Mirror
- Foot Massage
- Underwater Color Lighting
- Whirlpool Jets
- Air Jets
- Diverter
- Body Massage Jets
- Rainfall Shower
- Hand-held Shower
- Molded Seat
- Pressure Balance Valve (On Request)
- Adjustable Time Settings
- Control Panel with Remote
- Sliding Door
- Circulation Fan
- Fluorescent Light
- Interior Access Panel
- Drain Access Panel
- Tempered Glass
- Self-Cleaning Steam Generator

TECHNICAL INFORMATION

- **Materials:** Acrylic, Tempered Glass
- **Power Supply:** 220V
- **Steam Ready:** 2-5 MIN
- **Dimensions:** 53 x 53 x 88 IN

PLUMBING REQUIRMENTS

- The unit is equipped with hot and cold, metal braided ½ inch water supply hose with ½ national pipe thread
- Need to install hot and cold shutoffs with ½ -male national pipe thread (not included)
- Supply hoses are to connect from the faucet manifold on the unit to the shutoff valves
- All water jet features are pre plumbed with reinforced braided flexible supply hose

ELECTRICAL REQUIREMENTS

- **Steam box** - 3 KW/ 1- dedicated 12-2 wire (line 1, line 2, and ground) with 220 volt, 20amp GFCI breaker/ *this line for steam box only.*
- **Water pump** -.75 KW and **Air pump** -.5 KW- 1 dedicated 12-2 wire (line 1, line 2, and ground) with 220 volt, 20 amp GFCI breaker. The water and air pumps can both connect to this line.
- There is a length of wire from the steam box, water pump, and air pump to connect to the power source.

GENERAL INFORMATION

- Units come broken down in panels and are assembled with screws, nuts and bolts on site. All seams to be caulked with 100% silicone at room temperature (no latex caulking)
- **Note:** All shower bases need to be leveled in its final resting position, mark the placement, then pull base out and begin assembly. Glass on the front of tub does not open. For style only.
- It is advised to have base onsite before preparing drain location.

